

**SteelFiber**  
STEEL FIBER COMPOSITE

SteelFiber Iron Shaft Models and Specs:

SHAFT	FLEX	LENGTH	WEIGHT	TORQUE	TIP OD	BUTT OD	PARALLEL TIP	BEND POINT
SteelFiber i70	Stiff	41"	74gr	3.0	.370"	.600"	5.5"	MidDLow
SteelFiber i70	Regular	41"	74gr	3.3	.370"	.600"	5.5"	MidDLow
SteelFiber i70	Senior	41"	74gr	3.5	.370"	.600"	5.5"	MidDLow
SteelFiber i70	Ladies	41"	74gr	3.5	.370"	.600"	5.0"	Low
SteelFiber i70cw*	Stiff	40"Ø36.5"	70gr	3.4Ø2.8	.355"	.600"	n/a	MidDLow
SteelFiber i70cw*	Regular	40"Ø36.5"	70gr	3.4Ø2.8	.355"	.600"	n/a	MidDLow
SteelFiber i70cw*	Senior	40"Ø36.5"	70gr	3.5Ø2.9	.355"	.600"	n/a	MidDLow
SteelFiber i80	X-Stiff	41"	85gr	2.3	.370"	.600"	5.5"	Mid
SteelFiber i80	Stiff	41"	85gr	2.8	.370"	.600"	5.5"	Mid
SteelFiber i80	Regular	41"	85gr	2.9	.370"	.600"	5.5"	Mid
SteelFiber i80	Senior	41"	85gr	3.0	.370"	.600"	5.5"	Mid
SteelFiber i80	Ladies	41"	85gr	3.1	.370"	.600"	5.5"	Mid
SteelFiber i80cw*	Stiff	40"Ø36.5"	85gr	2.9Ø2.5	.355"	.600"	n/a	Mid
SteelFiber i80cw*	Regular	40"Ø36.5"	85gr	2.9Ø2.5	.355"	.600"	n/a	Mid
SteelFiber i95	X-Stiff	41"	95gr	2.2	.370"	.600"	5.25"	HighDMid
SteelFiber i95	Stiff	41"	95gr	2.4	.370"	.600"	5.25"	HighDMid
SteelFiber i95	Regular	41"	95gr	2.5	.370"	.600"	5.25"	Mid
SteelFiber i95cw*	X-Stiff	40"Ø36.5"	95gr	2.3Ø1.8	.355"	.600"	n/a	HighDMid
SteelFiber i95cw*	Stiff	40"Ø36.5"	95gr	2.4Ø2.0	.355"	.600"	n/a	HighDMid
SteelFiber i95cw*	Regular	40"Ø36.5"	95gr	2.5Ø2.1	.355"	.600"	n/a	Mid
SteelFiber i110	X-Stiff	41"	110gr	1.9	.370"	.602"	5.25"	HighDMid
SteelFiber i110	Stiff	41"	110gr	1.9	.370"	.602"	5.25"	HighDMid
SteelFiber i110	Regular	41"	110gr	2.1	.370"	.600"	5.25"	Mid
SteelFiber i110cw*	X-Stiff	40"Ø36.5"	110gr	1.9Ø1.5	.355"	.605"	n/a	HighDMid
SteelFiber i110cw*	Stiff	40"Ø36.5"	110gr	1.9Ø1.5	.355"	.605"	n/a	HighDMid
SteelFiber i110cw*	Regular	40"Ø36.5"	110gr	2.1Ø1.7	.355"	.605"	n/a	Mid
SteelFiber i125	Stiff	41"	125gr	2.1	.370"	.600"	4.5"	HighDMid
SteelFiber i125cw*	X-Stiff	40"Ø36.5"	125gr	1.8Ø1.4	.355"	.602"	n/a	HighDMid
SteelFiber i125cw*	Stiff	40"Ø36.5"	125gr	1.8Ø1.4	.355"	.600"	n/a	HighDMid

\*Taper Tip cw-Constant Weight

SteelFiber Iron Shaft Tip Trimming Instructions:

SHAFT	11*	21*	31*	41*	51*	61*	71*	81*	91*	PW*
SteelFiber i70	0"	0"	.5"	1.0"	1.5"	2.0"	2.5"	3.0"	3.5"	3.5"
SteelFiber i80	0"	0"	.5"	1.0"	1.5"	2.0"	2.5"	3.0"	3.5"	3.5"
SteelFiber i95	0"	0"	.5"	1.0"	1.5"	2.0"	2.5"	3.0"	3.5"	3.5"
SteelFiber i110	0"	0"	.5"	1.0"	1.5"	2.0"	2.5"	3.0"	3.5"	3.5"
SteelFiber i125	0"	0"	.5"	1.0"	1.5"	2.0"	2.5"	3.0"	3.5"	3.5"

\*All Taper Tip shafts (.355" tip) are Butt Trim Only

\*Tip trim can be adjusted to fine tune playing characteristics.

\*Tip trim should not exceed (Parallel Tip - Hosel Depth).

\*Perform tip trim and then butt trim to final playing length.